COMPACT RELAYS

RH SERIES

Features:

- SPDT through 2PDT, 10A contacts.
- Compact power type relays.
- 10A contact capacity.
- Compact size saves space.
- High switching capacity.
- Blade style terminals.
- DIN rail or surface mount base.



RH1B-1PDT



RH2B-2PDT

RH COMPACT RELAYS - 1 POLE

Rating (A)	Coil Voltage	Relay Type	Description	Part No.
10	12VAC	RH1 1PDT Relay		RH1B-UAC12
	24VAC			RH1B-UAC24
	110VAC			RH1B-UAC110
	240VAC			RH1B-UAC240
	6VDC			RH1B-UDC6
	12VDC			RH1B-UDC12
	24VDC			RH1B-UDC24
	32VDC			RH1B-UDC32
	48VDC			RH1B-UDC48
	110VDC			RH1B-UDC110
	12VAC		with LED indicator	RH1B-ULAC12
	24VAC		with LED indicator	RH1B-ULAC24
	110VAC		with LED indicator	RH1B-ULAC110
	240VAC		with LED indicator	RH1B-ULAC240
	12VDC		with LED indicator	RH1B-ULDC12
	24VDC		with LED indicator	RH1B-ULDC24
	48VDC		with LED indicator	RH1B-ULDC48
	110VDC		with LED indicator	RH1B-ULDC110
	24VDC		with diode & LED	RH1B-ULD-DC24

RH COMPACT RELAYS - 2 POLE

	6VAC			RH2B-UAC6
	12VAC			RH2B-UAC12V
	24VAC			RH2B-UAC24
	32VAC			RH2B-UAC32
	50VAC			RH2B-UAC50
	110VAC			RH2B-UAC110-120
	240VAC			RH2B-UAC220-240
	12VDC			RH2B-UDC12
	24VDC			RH2B-UDC24
	32VDC			RH2B-UDC32
	48VDC			RH2B-UDC48
	110VDC			RH2B-UDC100-110
	125VDC			RH2B-UDC125V
	12VAC		with LED indicator	RH2B-ULAC12
	24VAC		with LED indicator	RH2B-ULAC24
	110VAC		with LED indicator	RH2B-ULAC110
4.0	240VAC	RH2 2PDT Relay	with LED indicator	RH2B-ULAC240
10	12VDC		with LED indicator	RH2B-ULDC12
	24VDC		with LED indicator	RH2B-ULDC24
	48VDC		with LED indicator	RH2B-ULDC48
	110VDC		with LED indicator	RH2B-ULDC110
	125VDC		with LED indicator	RH2B-ULDC125
	12VDC		with diode	RH2B-UD-DC12
	24VDC		with diode	RH2B-UD-DC24
	48VDC		with diode	RH2B-UD-DC48
	110VDC		with diode	RH2B-UD-DC110
	12VDC		with diode & LED	RH2B-ULD-DC12
	24VDC		with diode & LED	RH2B-ULD-DC24
	48VDC		with diode & LED	RH2B-ULD-DC48
	110VDC		with diode & LED	RH2B-ULD-DC110
	125VDC		with diode & LED	RH2B-ULD-DC125
	110VAC		with indicator & Check button	RH2B-ULC-AC110V
	240VAC		with indicator & Check button	RH2B-ULC-AC240V
	24VDC		with indicator & Check button	RH2B-ULC-DC24

COMPACT RELAYS

RH SERIES

Features:

- 3PDT through 4PDT, 10A contacts.
- Compact power type relays.
- 10A contact capacity.
- Compact size saves space.
- High switching capacity.
- Blade style terminals.
- DIN rail or surface mount base.



RH3B-3PDT

RH4B-4PDT



SH1B-05C



SH2B-05C



SH3B-05C



SH4B-05C

RH COMPACT RELAYS - 3 POLE

Rating (A)	Coil Voltage	Relay Type	Description	Part No.
	12VAC	- - - - RH3 3PDT Relay - -		RH3B-UAC12
	24VAC			RH3B-UAC24
	110VAC			RH3B-UAC110
	240VAC			RH3B-UAC240
	12VDC			RH3B-UDC12
	24VDC			RH3B-UDC24
10	32VDC			RH3B-UDC32
10	48VDC			RH3B-UDC48
	110VDC			RH3B-UDC110
	24VAC		with LED indicator	RH3B-ULAC24
	110VAC		with LED indicator	RH3B-ULAC110
	240VAC		with LED indicator	RH3B-ULAC240
	24VDC		with LED Indicator	RH3B-ULDC24
	110VDC		with LED indicator	RH3B-ULDC110

RH COMPACT RELAYS - 4 POLE

10	24VAC			RH4B-UAC24
	110VAC	_		RH4B-UAC110
	120VAC			RH4B-UAC120
	240VAC	_		RH4B-UAC240
	12VDC			RH4B-UDC12
	24VDC			RH4B-UDC24
	32VDC	_		RH4B-UDC32
	48VDC	DUIA ADDT Delete		RH4B-UDC48
	110VDC	RH4 4PDT Relay —		RH4B-UDC110
	125VDC	_		RH4B-UDC125V
	24VAC	_	with LED indicator	RH4B-ULAC24
	110VAC		with LED indicator	RH4B-ULAC110
	240VAC	_	with LED indicator	RH4B-ULAC240
	12VDC		with LED indicator	RH4B-ULDC12
	24VDC		with LED indicator	RH4B-ULDC24
	125VDC		with LED indicator	RH4B-ULDC125

BASE FOR RH RELAYS

Description	Part No.
Base for RH1B (5 pin)	SH1B-05C
Base for RH2B (8 pin)	SH2B-05C
Base for RH3B (11 pin)	SH3B-05C
Basae for RH4B (14 pin)	SH4B-05C

