

OTHER TERMINAL BLOCKS



CHV4U

HIGH VOLTAGE (1000V) SCREW CLAMP 4mm²

Description	Part No.
Conductor cross section stranded, 0.2 - 4mm²	CHV4U
Dimensions (L x W x H), 52 x 6 x 63.4mm	
Colour "grey", 1000V/32A	
Connection: High voltage, feed through.	

ACCESSORIES

Marking tag: K6 size	
Endplate:	EPUSC
Separation plate:	SP2.5/4UN
End clamp:	CA702
Non-insulated shorting link:	CA623/*
Insulated shorting link:	CA643/*

* Specify 2, 3, 4, or 10 way at time of order.



CHV6U

HIGH VOLTAGE (1000V) SCREW CLAMP 6mm²

Description	Part No.
Conductor cross section stranded, 0.2 - 6.0mm²	CHV6U
Dimensions (L x W x H), 52 x 8 x 63.4mm	
Colour "grey", 1000V/41A	
Connection: High voltage, feed through.	

ACCESSORIES

Marking tag: K8 size	
Endplate:	EPUSC
Separator plate:	SP2.5/4UN
End clamp:	CA702
High end clamp:	CA802
Non-insulated shorting link:	CA624/**

** Specify 2, 3, 4, or 10 way at time of order.



CHV10U

HIGH VOLTAGE(1000V) SCREW CLAMP 10mm²

Description	Part No.
Conductor cross section stranded, 0.2 - 10.0mm²	CHV10U
Dimensions (L x W x H), 52 x 10 x 63.4mm	
Colour "grey", 1000V/57A	
Connection: High voltage, feed through.	


ACCESSORIES

Marking tag: K10 size	
Endplate:	EPUSC
Separator plate:	SP2.5/4UN
End clamp:	CA702
High end clamp:	CA802
Non-insulated shorting link:	CA625/**

** Specify 2, 3, 4, or 10 way at time of order.

EPUSC	SP2.5/4UN	CA702	CA802	CA623/* CA624/** CA625/**	CA643/*
-------	-----------	-------	-------	---------------------------------	---------

OTHER TERMINAL BLOCKS



STH4

HINGE TYPE STUD TERMINAL BLOCK LUG CONNECTION

6mm²

Description	Part No.
Conductor cross section stranded, 1.5 - 6mm ²	STH4
Dimensions (L x W x H), 46 x 11 x 52.2mm	
Colour "grey", 1000V/41A	
Stud size: M4	
Connection: Feed through.	

ACCESSORIES

Marking tag: K10 size	
Endplate:	EPSTH4
End clamp:	CA702
Insulated shorting link: 2 way:	CA514/14-2
3 way:	CA514/14-3
4 way:	CA514/14-4



CSTSN6U

STUD TYPE STUD TERMINAL BLOCK LUG CONNECTION

35mm²

Description	Part No.
Conductor cross section stranded, 1.5 - 35mm ²	CSTSN6U
Dimensions (L x W x H), 50 x 17 x 40.7mm	
Colour "grey", 1000V/125A	
Stud size: M6	
Connection: Feed through.	

ACCESSORIES

Marking tag: K2B4 size	
Endplate:	EPCSTSU
End clamp:	CA702
Insulated shorting link: 2 way:	CA514/8-2
3 way:	CA514/8-3
4 way:	CA514/8-4



CDB6/3*

DISTRIBUTION TERMINAL BLOCK

6mm²

Description	Part No.
Conductor cross section stranded, 1.5 - 6mm ²	CDB6/3*
Input wire size, 25mm ²	
Dimensions (L x W x H), 80 x 48 x 43mm	
Colour "grey", 800V	
Input 100A (25mm ² cable)	
Total output per terminal 82A (1.5 - 6mm ² cable)	
Connection: Distribution	

* Other output configurations available on request.

				
EPSTH4 EPCSTSU	CA702	CA514/14-2 CA514/8-2	CA514/14-3 CA514/8-3	CA514/14-4 CA514/8-4