

DOUBLE LEVEL TERMINAL BLOCKS



CDL4UN(I.S)

DOUBLE LEVEL TERMINAL BLOCKS
SCREW CLAMP

4mm²

Description	Part No.
Conductor cross section stranded, 0.2 - 4.0mm ²	CDL4UN(I.S)
Dimensions (L x W x H), 57 X 6 X 59.5 mm	
Colour "grey", 800V/32A	
Connection: Top and bottom level internally shorted.	

ACCESSORIES

Marking tag: K6 size	
Endplate:	EPCDL4UN
Separator plate:	SPCDL4U
End clamp:	CA702
	CA202
Non-insulated shorting link:	CA722/*
Insulated shorting link:	CA742/*
Comb insulated shorting link:	CA714/**

* Specify 2, 3, 4, 10 or 100 way at time of order.

** Specify 2, 3, 4 or 10 way at time of order.



ODL4U

Description	Part No.
Conductor cross section stranded, 0.2 - 4.0mm ²	ODL4U
Dimensions (L x W x H), 68 x 6 x 65mm	
Colour "grey", 800V/32A	
Connection: Feed through, top and bottom levels. Top level is offset from bottom level	

ACCESSORIES

Marking tag: K6 size	
Endplate:	EPODL4U
End clamp:	CA702
	CA202
Non-insulated shorting link:	CA727/**
Insulated shorting link:	CA747/**
Comb insulated shorting link:	CA714/**

** Specify 2, 3, 4 or 10 way at time of order.

							
EPCDL4UN	SPCDL4U	CA702	CA202	CA722/*	CA727/*	CA742/*	CA714/**
EPODL4U						CA747/*	

DOUBLE LEVEL TERMINAL BLOCKS



CDL4UN

DOUBLE LEVEL TERMINAL BLOCKS SCREW CLAMP

4mm²

Description	Part No.
Conductor cross section stranded, 0.2 - 4.0mm ²	CDL4UN
Dimensions (L x W x H), 57 x 6 x 59.5mm	
Colour "grey", 800V/32A	
Connection: Feed through, top and bottom levels	

ACCESSORIES

Marking tag: K6 size	
Endplate:	EPCDL4UN
Separator plate:	SPCDL4U
End clamp:	CA702
	CA202
High end clamp:	CA802
Non-insulated shorting link:	CA722/*
Insulated shorting link:	CA742/*
Comb insulated shorting link:	CA714/**

* Specify 2, 3, 4, 10 or 100 way at time of order.

** Specify 2, 3, 4 or 10 way at time of order.



CDLG2.5

DOUBLE LEVEL with EARTH CONNECTION SCREW CLAMP

2.5mm²

Description	Part No.
Conductor cross section stranded, 0.2 - 2.5mm ²	CDLG2.5
Dimensions (L x W x H), 71.1 x 6 x 53mm	
Colour "grey", green/yellow, 500V/24A	
Connection: Double level feed through with Earth.	


ACCESSORIES

Marking tag: K2G size	
Endplate:	EPCDLG2.5
Separator plate:	SPCDLG2.5
End clamp:	CA702
	CA202
High end clamp:	CA802
Non insulated shorting link:	CA627/**
Comb insulated shorting link:	CA715/**

** Specify 2, 3, 4 or 10 way at time of order.

								
EPCDLG2.5 EPCDL4UN	SPCDLG2.5 SPCDL4U	CA702	CA202	CA802	CA722/*	CA627/**	CA742/*	CA714/** CA715/**

DOUBLE LEVEL TERMINAL BLOCKS



CDLG4

DOUBLE LEVEL with EARTH CONNECTION
SCREW CLAMP

4mm²

Description	Part No.
Conductor cross section stranded, 0.2 - 4.0mm ²	CDLG4
Dimensions (L x W x H), 57 x 6 x 59mm	
Colour "grey", green/yellow, 500V/32A	
Connection: Double level feed through with Earth.	

ACCESSORIES

Marking tag: K6 size	
Endplate:	EPCDL4UN
Seperator plate:	SPCDL4U
End clamp:	CA702
	CA202
High end clamp:	CA802
Non insulated shorting link:	CA722/*
Insulated shorting link:	CA742/*
Comb insulated shorting link:	CA714/**

* Specify 2, 3, 4, 10 or 100 way at time of order.

** Specify 2, 3, 4 or 10 way at time of order.

