

## TRIPLE LEVEL TERMINAL BLOCKS



CTL2.5U

### TRIPLE LEVEL TERMINAL BLOCKS SCREW CLAMP

2.5mm<sup>2</sup>

Description	Part No.
Conductor cross section stranded, 0.2 - 2.5mm <sup>2</sup>	CTL2.5U <sup>1</sup>
Dimensions (L x W x H), 84 x 6 x 68mm	
Colour "gery", 500V/24A	
Connection: Feed through all levels.	

#### ACCESSORIES

Marking tag: K2 size	
Endplate:	EPCTL2.5U
End clamp:	CA702
	CA202
High end clamp:	CA802
Non-insulated shorting link:	CA722/*
Comb insulated shorting link:	CA715/**

<sup>1</sup> LED indication version also available.

\* Specify 2, 3, 4, 10 or 100 way at time of order.

\*\* Specify 2, 3, 4 or 10 way at time of order.



CTLG2.5

### TRIPLE LEVEL with EARTH CONNECTION SCREW CLAMP

2.5mm<sup>2</sup>

Description	Part No.
Conductor cross section stranded, 0.2 - 2.5mm <sup>2</sup>	CTLG2.5
Dimensions (L x W x H), 87.5 x 6 x 66mm	
Colour "gery", green/yellow, 440V/24A	
Connection: Triple level feed through with Earth.	

#### ACCESSORIES

Marking tag: K2G size	
Endplate:	EPCTLG2.5
End clamp:	CA702
	CA202
Non-insulated shorting link:	CA627/*
Insulated shorting link:	CA647/*
Comb insulated shorting link:	CA715/*

\* Specify 2, 3, 4 or 10 way at time of order.

							
EPCTL2.5U EPCTLG2.5	CA702	CA202	CA802	CA722/*	CA627/*	CA647/*	CA715/**