

SPRING LOADED TERMINAL BLOCKS



CTS4USC

SPRING LOADED SCREW CLAMP

4mm²

Description	Part No.
Conductor cross section stranded, 0.2 - 4.0mm ²	CTS4USC
Dimensions (L x W x H), 52 x 6 x 63.4mm	
Colour "grey", 1000V/32A	
Connection: Safety spring loaded, feed through.	

ACCESSORIES

Marking tag: K6 size	
Endplate:	EPUSC
Separation plate:	SP2.5/4UN
End clamp:	CA702
Non-insulated shorting link:	CA623/*

* Specify 2, 3, 4, or 10 way at time of order.



CTS10USC

SPRING LOADED SCREW CLAMP

10mm²

Description	Part No.
Conductor cross section stranded, 0.2 - 10.0mm ²	CTS10USC
Dimensions (L x W x H), 52 x 10 x 63.4mm	
Colour "grey", 1000V/57A	
Connection: Safety spring loaded, feed through.	

ACCESSORIES

Marking tag: K10 size	
Endplate:	EPUSC
Separation plate:	SP2.5/4UN
End clamp:	CA702
High end clamp:	CA802
Non-insulated shorting link:	CA625/**

** Specify 2, 3, 4 or 10 way at time of order.

