

M SERIES MINI CONTACTORS

4 TO 5.5kW

Features:

- Space saving solution.
- Control circuit: AC or DC operated.
- Add-on auxiliary contact blocks for front or side mounting (up to 6 additional contacts).
- Suitable for DIN or wall mounting.



MC1A310AT...



MC1C310AT...

3 POLE - WITH SCREW TERMINALS

AC OPERATED

400V AC-3 (kW)	400V AC-1 (A)	Auxiliary			Part No.
		NO	NC		
3 N.O. Main Poles					
4	20	1	0		MC1A310AT ☐
		0	1		MC1A301AT ☐
5.5	20	1	0		MC2A310AT ☐
		0	1		MC2A301AT ☐

☐ To complete Part Number, add the required voltage code

Code	1	N	W
Voltage AC 50Hz	24	220...240	415...440

DC OPERATED

400V AC-3 (kW)	400V AC-1 (A)	Auxiliary		Voltage DC	Part No.
		NO	NC		
3 N.O. Main Poles					
4	20	1	0	24	MC1C310ATD
		0	1		MC1C301ATD
5.5	20	1	0		MC2C310ATD
		0	1		MC2C301ATD

4 POLE - WITH SCREW TERMINALS

AC OPERATED

400V AC-3 (kW)	400V AC-1 (A)	Auxiliary		Part No.
		NO	NC	
4 N.O. Main Poles				
4	20	0	0	MC1A400AT ☐
5.5	20	0	0	MC2A400AT ☐
2 N.O. + 2 N.C. Main Poles				
4	20	0	0	MC1AB00AT ☐

☐ To complete Part Number, add the required voltage code

Code	1	N
Voltage AC 50Hz	24	220 ... 240

- Other contact configuration available. Please consult your ABB local sales organization.



MC1A400AT...